

OPT SPECIAL SERIES BULLET CAMERA

IP Bullet Network Camera

SYSTEM OVERVIEW



The OPTOKON SPECIAL series is a line of surveillance cameras that utilize advanced H.265 encoding technology to improve video compression, resulting in reduced bandwidth usage and storage requirements. This technology allows for more efficient video transmission, without compromising on the quality of the video captured.

In addition to the improved encoding technology, the special series also includes features such as starlight technology, which enhances low-light performance, as well as smart IR technology, which automatically adjusts the intensity of the infrared illuminator based on the distance of the subject. These features ensure that the cameras are capable of capturing high-quality video even in challenging lighting conditions.

Furthermore, the cameras in the OPTOKON SPECIAL SERIES BULLET are designed to be fully protected from dust and water, with an IP67 rating, and are vandal-resistant to IK10 standard. This makes them suitable for use in a wide range of environments, including outdoor settings where they may be exposed to harsh weather conditions or potential tampering.

OPTOKON SPECIAL SERIES BULLET supports PoE and PoC power supply technology which has greatly simplified construction and wiring. OPTOKON technology offer a new way to accomplish long distance transmission between IP camera and network switch. It allows more flexible surveillance system design, improves reliability, and saves construction and wiring cost.



- **5MP & 8/4K Megapixel progressive scan**
- **Support ONVIF**
- **8 pcs OSRAM IR Array LEDs**
- **IR Distance: 50 meter**
- **IP 67**

Environmental

Optokon cameras are designed to operate in extreme temperature environments, making them suitable for use in a wide range of applications, including outdoor surveillance and industrial monitoring. These cameras are rated for use in temperatures ranging from -30° C to +60° C (-22° F to +140° F), which is a wide temperature range that covers most extreme weather conditions. In addition to the wide temperature range, Optokon cameras also have a high level of humidity resistance, with a 95% humidity rating. This means that the cameras can operate in environments with high levels of moisture, such as near bodies of water or in areas with high humidity levels. The ability of Optokon cameras to operate in extreme temperature and humidity environments makes them highly durable and reliable, even in harsh conditions. This means that they can be used in a wide range of settings, including industrial plants, oil and gas facilities, and other outdoor environments where reliable surveillance and monitoring is critical.

Optokon cameras' support for PoE and PoC technologies provides a cost-effective and flexible solution for surveillance system installations, with simplified construction and wiring, improved reliability, and reduced long-term operating costs.

OPT SPECIAL SERIES BULLET CAMERA

IP Bullet Network Camera

TECHNICAL SPECIFICATION

| Model No. | | OPT-SP-IPM5905-A10 | OPT-SP-IPM5908-A10 |
|---------------------|---|--|---|
| Camera Type | | Long Range Infrared Bullet IP Camera | |
| System | | Embedded RTOS design | |
| Camera | Effective Pixels | 5.0 Mega Pixels | 8.0 Megapixels |
| | | Main stream:2592*1944 | Main stream:3840*2160 |
| | | Sub stream:704*576 | Sub stream:704*576 |
| | Frames Rates | PAL:25fps NTSC: 30fps | PAL:15fps NTSC: 15fps |
| | Image Sensor | 1/2.7" CMOS, WDR | 1/2.8" SONY, WDR |
| | DSP | Dual core 32-bit DSP | Dual core 32-bit DSP |
| | | HI3516C | HI3516 |
| | Min. Illumination | Color 0.001Lux@F1.2 | Color 0.01Lux@F1.2 |
| B/W 0.0001 Lux@F1.2 | | B/W 0.001 Lux@F1.2 | |
| Adjust Parameters | WDR,BLC,DNR,AE,AGC,D&N,Mirror,Flip,etc. | | |
| Video | Compression | 265+/H.265/H.264 Dual Stream | 265+/H.265/H.264 Dual Stream |
| | Stream | support dual stream,AVI format | support dual stream,AVI format |
| | Bit Rate | support 0.1M ~8Mbps bit rate adjustable | support 0.1M ~8Mbps bit rate adjustable |
| | Frame Rates | support 1~30fps adjust | support 1~30fps adjust |
| Audio | Input and output | 1ch input(micphone),1ch output(Speaker&micphone) Optional | |
| | Compression | G.711 compression,support two-way audio intercom,support audio and video synchronized output | |
| Alarm | Types | Motion Detection, Video Blind , Video Loss | |
| Network | WEB Browser | Support WEB remote config(IE, Safari, Google Chrome, Firefox etc.) | |
| | Smart Phone | mobile remote Monitoring (iPhone,Android,...) | |
| | CMS Software | Uniform CMS Software(multiple devices management system) | |
| | Network | 10/100M,Support RTSP/FTP/DHCP/DDNS/NTP/UPnP/SMTP | |
| | ONVIF | Support | |

| | | |
|----------------|----------------------|--|
| General | Language | 20 kinds of languages such as English, Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, S-Chinese, T-Chinese and Turkish |
| | IR Cut Filter | Set of double light switch IR-CUT filter |
| | Lens Mount | Autofocus Lens 5-50mm |
| | Infrared Luminary | 8 pcs SMD LED |
| | Infrared Wavelength | 850nm |
| | Illuminate Distance | 50m |
| | Waterproof Criterion | IP 67 |
| | I/O Connector | 1*DC Connector ,1* RJ45(10/100M Network) |
| | Supplied Voltage | DC12V/PoE(802.3af/820.3at) |
| | Power Consumption | IR On: 600mA max., IR Off: Less than 200mA |
| | Housing Material | Double shell, Aluminum die casting |
| | Working Environment | -10°C~+60°C, 10%~90% (Built in Heater being optional added for environment lower than -20°) |
| | Weight | 1.5kg |